

PLEASE POST THESE SAFETY RULES NEAR MACHINE FOR REFERENCE

SAFETY RULES for



MOTORIZED MITER BOX

- 1. WEAR eye protection.
- 2. DO NOT operate saw without guards in place.
- 3. DON'T use the tool in the presence of flammable liquids or gases.
- 4. CHECK the blade carefully for cracks or damage before operation. Replace cracked or damaged blade immediately.
- 5. USE ONLY flanges specified for this tool.
- BE CAREFUL not to damage the arbor, flanges (especially the installing surface) or bolt.
 Damage to these parts could result in blade breakage.
- 7. MAKE SURE that the turn base is properly secured so it will not move during operation.
- 8. REMOVE chips, small pieces, etc. from the table top before operation.
- 9. DO NOT CUT USED LUMBER. Inspect lumber for any nail, staples, and metal objects.
- 10. MAKE SURE the shaft lock is released before the switch is turned on.
- 11. BE HELP that the blade does not contact the turn base in the lowest position.

- 12. HOLD the handle firmly. Be aware that the saw moves up or down slightly during start-up and stopping.
- 13. DO NOT perform any operation freehand.

 The workpiece must be secured firmly against the turn base and guide fence during all operations.
- 14. KEEP hands out of path of saw blade. Avoid contact with any coasting blade. It can still cause severe injury.
- 15. NEVER reach around saw blade.
- 16. MAKE sure the blade is not contacting the workpiece before the switch is turned on.
- 17. BEFORE using the tool on an actual workpiece, let it run for a while. Watch for vibration or wobbling that could indicate poor installation or a poorly balanced blade.
- 18. WAIT until the blade attains full speed before cutting.
- 19. STOP operation immediately if you notice anything abnormal.
- 20. DO NOT attempt to lock the trigger in the on position.